

ezlastic

Elastomeric Finish Coat

DESCRIPTION

EZLASTIC is a highly elastic, weather-resistant, decorative wall coating specifically designed for application over portland cement plaster, cast-in-place concrete, and other approved substrates. EZLASTIC is available in four textures, a variety of colors, and is integrally colored and fade resistant.

ADVANTAGES

- 100% Acrylic
- Elastomeric – bridges hairline cracks
- Excellent adhesion
- Ready-mixed, no additives
- Water-based for easy clean up

PREPARATION

The surface must be fully cured, dry, and free of dust. For best floating and texture definition, remove all protruding base coat greater than 1/16". A smooth surface, free from protrusions and pits greater than 1/16" will allow for easier floating and a more uniform texture pattern. EZPRIME is applied prior to application of EZLASTIC. EZPRIME improves adhesion, coverage, color consistency and inhibits efflorescence. EZPRIME may be applied with a paint roller or brush.

MIXING

Mix with a clean, rust-free electric drill and paddle. A small amount of clean water may be added to aid workability. Do not add more than 8 oz. of water.

APPLICATION

- Apply with a clean, stainless steel trowel.
- Plan the finish application so enough workers are available to finish entire sections of wall area at one time, uninterrupted. Inspect the cement substrate and correct all imperfections before applying the finish.
- Work in pairs, with the first person applying the finish to the wall and the second person floating the finish to the desired texture.
- Apply finish in a continuous application, always working away from a wet edge.
- Avoid installing separate batches of finish side-by-side.
- Interrupt application at natural breaks in construction, i.e. expansion joints, changes of plane, etc.
- Avoid application in direct sunlight and excessive wind, whenever possible.
- When spreading finish, apply only the pressure required so that the thickness is gauged by the largest aggregate particles.

CURING

EZLASTIC dries overnight under normal conditions. The drying time is affected by air temperatures, relative humidity, and coating thickness.

CLEAN-UP

Clean all tools and equipment with water. Do not allow finish to harden on tools.

DISPOSAL

Dispose in accordance with local, state, and/or federal regulations.

COVERAGE

EZLASTIC Smooth 140-180 sq. ft.

EZLASTIC Fine 120-150 sq. ft.

EZLASTIC Medium 100-120 sq. ft.

EZLASTIC Swirl 100-120 sq. ft.

Coverage is approximate and will vary depending on substrate, details, and individual application.

PACKAGING

60 lb. (27.2 kg) plastic pail

STORAGE

Avoid direct sunlight and protect from extreme heat and freezing.

SHELF LIFE

12 months when properly stored and sealed

CAUTIONS AND LIMITATIONS

Hot or dry conditions limit the working time, accelerate drying and may require adjustments in the scheduling of work to achieve the desired results. Cool or damp conditions extend the working time, slow drying and may require added measures of protection against wind, dust, dirt, rain, and freezing. Surface temperatures must be above 40°F (4°C).

WARRANTY

This product is subject to a written limited warranty, which may be obtained free of charge from EZWALL. EZLASTIC is to be applied in accordance with all the manufacturer's specifications. EZWALL Coatings Inc. is unable to accept responsibility for job conditions, workmanship, climate, or damages due to transport.

ezwall
www.ezwallcoatings.com