

ezprime

Acrylic Primer

DESCRIPTION

EZPRIME is a water-based, tintable, acrylic primer which provides a flat, uniformly absorbent, color coordinated surface for application of EZLASTIC or EZCRYL finishes.

EZPRIME is recommended for the surface preparation of SP20, EZFIBER, interior drywall, concrete, masonry or stucco to color coordinate the substrate with the finish. EZPRIME enhances color consistency, reduces flashing, increases texture consistency, improves bond strength and coverage, and increases working time in hot and dry weather.

ADVANTAGES

- 100% Acrylic based
- Ready-mixed, no additives
- Water based for easy clean up
- Excellent adhesion

PREPARATION

Surfaces should not be below 40°F (4°C) and must be clean, dry, structurally sound, and free of efflorescence, grease, oil, form release agents, curing compounds, and any other deleterious materials.

MIXING

Mix with clean, rust-free, electric drill and paddle to a smooth, homogeneous consistency. Clean water may be added in small amounts, if necessary.

APPLICATION

EZPRIME may be applied with a brush, roller, or proper spray equipment in a continuous coat. Allow drying before applying EZWALL finishes.

CURING

EZPRIME dries within 4 hours under normal conditions. Drying times are affected by air temperatures, relative humidity, and coating thickness.

CLEAN-UP

Clean all tools and equipment with water. Do not allow the acrylic to harden on tools.

DISPOSAL

Dispose in accordance with local, state, and/or federal regulations.

COVERAGE

Approximately 800 square feet per 60 lb. pail, depending upon surface roughness and porosity of the substrate.

PACKAGING

60 lb. (27.2 kg) plastic pail

STORAGE

Avoid direct sunlight and protect from extreme heat and freezing temperatures.

SHELF LIFE

12 months when properly stored and sealed

CAUTIONS AND LIMITATIONS

Ambient air and surface temperatures for the application of EZPRIME must be 40°F (4°C) or higher and must remain at those temperatures for a minimum duration of 24 hours. EZPRIME should not be used as a finish coat. Use adequate ventilation and avoid prolonged skin contact. Wash skin thoroughly with warm water.

WARRANTY

This product is subject to a written limited warranty which may be obtained free of charge from EZWALL. EZPRIME is to be applied in accordance with all of the manufacturer's specifications. EZWALL Coatings Inc. is unable to accept responsibility for job conditions, workmanship, climate, or damages due to transport.

ezwall
www.ezwallcoatings.com